



## LONG RADIUS 90 DEGREE STREET ELBOW NAVSEA 802-5959353 App.B, MSS SP-119

304 and 316 STAINLESS STEEL  
Belled End



DIMENSIONS											
NOMINAL PIPE SIZE	OD	R	T	K (Tangent)	WEIGHT (lb)	NAVSEA		MSS		TORK P/N 304SS	TORK P/N 316SS
						R	T	R	T		
1/4	0.540	1.59	1.28	0.28	0.20	2.12	1.80	0.62		<a href="#">M123189</a>	<a href="#">M125971</a>
3/8	0.675	1.94	1.62	0.38	0.30	2.12	1.80	0.62		<a href="#">M123190</a>	<a href="#">M125972</a>
1/2	0.840	2.25	1.94	0.44	0.50	2.25	1.94	0.75		<a href="#">M123191</a>	<a href="#">M125973</a>
3/4	1.050	1.91	1.59	0.47	0.60	2.25	1.94	0.75		<a href="#">M123192</a>	<a href="#">M125974</a>
1	1.315	2.38	2.00	0.50	0.70	2.38	2.00	0.88		<a href="#">M123193</a>	<a href="#">M125975</a>
1 1/4	1.660	2.88	2.44	0.56	1.00	2.88	2.44	1.00		<a href="#">M123194</a>	<a href="#">M125976</a>
1 1/2	1.900	3.50	2.94	0.69	1.00	3.50	2.94	1.25		<a href="#">M123195</a>	<a href="#">M125977</a>
2	2.375	4.28	3.72	0.72	2.00	4.28	3.72	1.28		<a href="#">M123196</a>	<a href="#">M125978</a>
2 1/2	2.875	5.38	4.62	0.88	4.00	5.38	4.62	1.63		<a href="#">M123197</a>	<a href="#">M125979</a>
3	3.500	6.17	5.41	0.91	5.00	6.17	5.41	1.67		<a href="#">M123198</a>	<a href="#">M125980</a>
3 1/2	4.000	6.98	6.18	0.94	8.00	6.98	6.18	1.73		<a href="#">M123199</a>	<a href="#">M125981</a>
4	4.500	7.78	6.97	0.97	9.60	7.78	6.97	1.78		<a href="#">M123200</a>	<a href="#">M125982</a>
5	5.563	9.53	8.59	1.09	16.50	9.53	8.59	2.03		<a href="#">M123201</a>	<a href="#">M125983</a>
6	6.625	11.17	10.17	1.17	27.00	11.17	10.17	2.17		<a href="#">M123202</a>	<a href="#">M125984</a>
8	8.625	14.62	13.38	1.38	35.00	14.62	13.38	2.62		<a href="#">M123203</a>	<a href="#">M125985</a>
10	10.750	18.00	16.56	1.56	65.50	18.00	16.56	3.00		<a href="#">M123204</a>	<a href="#">M125986</a>
12	12.750	21.25	19.69	1.69	116.00	21.25	19.69	3.25		<a href="#">M123205</a>	<a href="#">M125987</a>